电机特性表 Specifications of Motor

电机类型	电机型号		功率	频率	电压	电流	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
	Motor Model	Gearhead	Power	Frequency	Voltage	Current	Starting Torque	Output g·cm	Speed r/min	Capacitor μF	Withstand Voltage V	Bearing	Intermediate Gear
[illegible]	6RK120A-A	6RF120GU-A	120	50	110	2.40	9500	9000	1300	35	250	6GU-K	6GM10X
				60	110	2.20	7900	7550	1550	30			
	[illegible]			[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]			
可逆型电机 Reversible motor	[illegible]	6RK120GU-C	120	60	220	1.10	7900	7550	1550	7	500	6GU-K	6GM10X
	6RK140[illegible]	6RK140GU-A	140	50	110	2.80	11000	10500	1300	40	[illegible]	[illegible]	[illegible]
	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

外形尺寸 Outline Dimension

型号 Model	减速比 Reduction Ratio	L1 (mm)	L2 (mm)	L3 (mm)	h (mm)
[illegible]6RK120	1:3~1:300	142	65	207	10
6IK/RK140A/GU	1:3~1:300	142	65	207	10

齿轮减速电机, Gear Motor

扭矩表 Torque Table (减速比 i=i)

(kg·cm 1kg·cm=0.098Nm(牛顿·米))

减速比	转速 : r/min	500	300	200	150	120	100	75	60	50	30	20	15	10	7.5	6	5	3
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]